

dB-3764B TWT Amplifier



7.6kW Pulsed
9.3 – 10.0 GHz



The dB-3764B is a TWT Amplifier (TWTA) operating in the X-band frequency range providing 7600 Watts peak power at a 5% maximum duty cycle. A wide-band, periodic permanent magnet (PPM)-focused, conduction-cooled TWT is used for power amplification. The high-voltage power supply (HVPS) section uses modular architecture and low-noise power supply topology utilizing high-efficiency solid-state power-conversion circuits. A highly stable, solid-state modulator is used for pulsing the TWT grid. An embedded micro-controller provides the interface, control and protection functions and status indication for the TWT Amplifier. RS-422 is the standard interface protocol for remote control.

Features

- X-band TWTA
- 9.3 to 10.0 GHz, 7.6 kW, 5% duty cycle

Applications

- Radars
- Test and measurement
- Antenna pattern and radar cross-section measurements

dB-3764B TWT Amplifier Specifications

Reliability by Design®

Electrical

Frequency Range	9.3 to 10.0 GHz
Output Power, Peak	7600 Watts, min.
Duty Cycle	5%, max.
PRF	50 kHz, max.
Pulse Width	0.2 to 100 µsec
RF Drive for Rated Power	0 dBm (1 milliwatt)
Harmonics	-50 dBc, max.
Noise and Non-Harmonic Spurious	-60 dBc
RF Rise and Fall Times	50 nsec
Input VSWR	1.6:1, max.
Output VSWR	2.5:1, max.
Load VSWR	2.5:1, Continuous, no damage
Input Pulse	Differential, RS-422
Prime Power	115/200 VAC, 3 Phase, 400 Hz
Protection	Helix Over-Current/Arc Cathode Over-Voltage High Reflected RF Power Over-Temperature (TWT and Power Supply) Excessive PRF, Pulse width or duty cycle Open Interlocks
Front Panel Display	Status, Faults
RF Power Sample	-50 dB
Instrument Control	Local (Front Panel) or Remote
Remote	RS-422

Mechanical

Connectors	
Prime Power	D38999/24WE8PN
I/O Interface	D38999/24WF18PN
I/O Control Interface	D38999/24WCE8PN
Test Connector	D38999/24E8PN
RF Input	TNC (F)
RF Input Sample	SMA (F)
RF Output	WR-90 Waveguide Flange
RF Output Sample	TNC (F)
Size	18.16" (W) x 10.62" (H) x 21.1" (D)
Weight	83 lbs, nominal
Cooling	Forced Air with integral fan

Environmental

Operating Temperature	-40° C to +50° C, ambient
Operating Altitude	Up to 30,000 feet ASL
Humidity	Up to 95% RH Non-Condensing

Options

- Custom Frequency Bands
- Different Prime Power Input
- Custom Protocol Interface
- RF Gain Control

Specifications subject to change without notice.



About dB Control

Established in 1990, dB Control Corp., a subsidiary of the Electronic Technologies Group (ETG) of HEICO Corp., supplies mission-critical, often sole-source, products worldwide to military organizations, as well as to major defense contractors and commercial manufacturers. dB Control designs and manufactures reliable high-power TWT Amplifiers (TWTAs), microwave power modules (MPMs), transmitters and power supplies with modulators for radar, electronic countermeasures (ECM) and data link applications. The company's high-power amplifiers use solid state, as well as vacuum electron devices and cover the 1 to 50 GHz frequency range. The modularity of dB Control's designs enables rapid configuration of custom products for a variety of platforms, including ground-based and high-altitude military manned and unmanned aircraft. dB Control has an outstanding record of successfully repairing, refurbishing and replacing tightly packaged high-voltage transformers, assemblies and power supplies. The company offers specialized contract manufacturing, transformer winding and testing, full vacuum encapsulation, pressure cure, conformal coating and repair depot services from its modern 40,000 square foot facilities in Fremont, California. www.dBControl.com

dB Control
a HEICO company
Reliability by Design®

